



# 6500

## Approved Luxury Vinyl Tile SPRAY ADHESIVE



### PRODUCT CHARACTERISTICS

**Spray-Lock® 6500** is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank, and Carpet Tile in commercial and residential applications.

**Spray-Lock® 6500** uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. 6500's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

**Spray-Lock® 6500** is a non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

### ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.020 g/ml VOC content
- Non-Toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors

### SUITABLE SUBSTRATES

**Spray-Lock® 6500** bonds approved LVT, LVP, and carpet tile to the following properly prepared smooth, flat, dust free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

### TECHNICAL CHARACTERISTICS

**Spray-Lock® 6500** provides immediate shear strength after installation allowing instant access to finished floor.

**Spray-Lock® 6500** is solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content. According to EPA Test Method 8260B.

**Spray-Lock® 6500** uses non-ozone-depleting HFC propellant.

**Spray-Lock® 6500** withstands 8 lbs. of vapor emissions, 90% RH and 11 pH.

\*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

# TECHNICAL DATA

CHEMICAL TYPE	Water-based Acrylic Blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-Flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	4 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 8 lbs/1,000 sq ft or 90% RH/11pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



## COVERAGE GUIDE

LVT, LVP, TILE | UPSIDE DOWN AEROSOL  
150-185 sq ft