



9500 PLATINUM

Approved VCT Flooring

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® 9500 Platinum is a versatile spray adhesive naturally suited for adhering approved Vinyl Composition Tile (VCT) in commercial and residential applications.

Spray-Lock® 9500 Platinum uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. 9500 Platinum's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

Spray-Lock® 9500 Platinum is a non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® 9500 Platinum bonds approved Vinyl Composition Tile (VCT) to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

Spray-Lock® 9500 Platinum provides immediate shear strength after installation, allowing instant access to finished floor.

Spray-Lock® 9500 Platinum is solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® 9500 Platinum uses non-ozone depleting HFC propellant.

Spray-Lock® 9500 Platinum withstands 10 lbs. of vapor emissions, 95% RH and 12 pH.

*Green Seal Certified: This product meets Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity. GreenSeal.org.

**According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	2 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 10 lbs/1,000 sq ft or 95% RH/12pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

VCT FLOORING | UPSIDE DOWN AEROSOL
170-190 sq ft